

1. Locate the clutch cable adjustor on the right side of the frame down tube.

for 2021 Models











Tools & Supplies Side Cutters

Small Straight Screwdriver

15 mm Wrench

EZ Clutch Adjustor Upgrade Kit

2. Remove the yellow plastic adjustor with a a pair of side cutters. Cut the plastic from the bottom and from the top. Be careful not to cut the cable wire.



3. Now remove the spring by spreading open the end of the spring and twisting it off of the wire.




4. The photo below shows the parts that you are removing from the stock upper cable.



WARNING: The rider's safety depends upon the correct installation of this kit. Use the appropriate service manual procedures. If the procedure is not within your capabilities or you do not have the correct tools, contact a dealer to perform the installation. Improper installation of this kit could result in death or serious injury.

Test brakes at low speed. If brakes are not operating properly, testing at high speeds can cause loss of control, which could result in death or serious injury.

5. Remove the O-ring from the adjustor. Align the slots on the two parts of the adjustor, then slide the wire into the slot.





6. Now install the o-ring by sliding it over the bottom of the cable and back into the groove on the adjustor.



7. The new adjustor should look like the picture below when installed. After adjusting the clutch, tighten the locking nut.



8. In the image below: On the left is the stock cable (before), and on the right is the new adjustor installed (after).

BEFORE

AFTER

Factory H-D Upper Clutch Cable FBI EZ Clutch Adjustor Upgrade Kit



